







Bervic Engineering Company Pty Ltd

258 Boundary Road, Braeside, Victoria 3195 Australia
 Tel: +61 3 9587 2766 Fax: +61 3 9587 3485
 E-mail: bervic@bervic.com.au www.bervic.com.au


For the isolation of service loads during replacements and repairs use

BERVIC Live Line and Earthing Clamps

Part No.	Clamp Type	Description
BST		<ul style="list-style-type: none"> A heavy duty fully shrouded clamp with T-handle The patented shrouded spindle is fully protected to prevent thread damage, dirt and airbourne pollutants interfering with the function of the clamp Main cable capacity: \varnothing 5–19mm Split bolt capacity: up to 2 tap conductors \varnothing 5–8mm
BT		<ul style="list-style-type: none"> A heavy duty clamp with T-handle Main cable capacity: \varnothing 5–19mm Split bolt capacity: tap conductor \varnothing 5–8mm
BL12		<ul style="list-style-type: none"> A heavy duty clamp with T-handle Main cable capacity: \varnothing 5–19mm \varnothing 12mm hole in body to take cable lug and bolt
BP		<ul style="list-style-type: none"> A heavy duty clamp with screw driver handle Main cable capacity: \varnothing 5–19mm Split bolt capacity: tap conductor \varnothing 5–8mm



BST Clamp
 Patent protected
 (Patent No. 699099)



BT Clamp



BP Clamp

- All Bervic clamps are made from a forged brass body.
- The stainless steel spindle has a 12mm thread to ensure a strong clamping force and to prevent the clamp from becoming loose due to vibration.
- The clamping block is also constructed from brass to ensure maximum conductivity.
- All Bervic clamps have been tested to AS 1154.1-1985 by a NATA approved laboratory.
- All clamps are proudly made in Australia.



Quality
 ISO 9001